

Product Information:

- Designed and recommended for wet operation
- Temperature regulation via thermostat (70°C - 80°C) and temperature gauge
- In-tank temperature probes for accurate measurement
- Multiple elements for even heat distribution and ongoing operation
- Air insulated, double skinned tank for energy efficient heating
- Manual water fill with tank sloped to ball valve operated drain
- Robust stainless steel construction
- Accessories sold separately
- NOTE: All Woodson Bain Maries are designed for use with Woodson pans. Other suppliers pans may fit, however this is not guaranteed
- Optional drop-in kits and trolleys available
- **12-month onsite warranty**



Specifications

Model	W.BMA22	W.BMA23	W.BMA24	W.BMA25	W.BMA26
W x D x H (mm)	705 x 600 x 245*	1030 x 600 x 245*	1355 x 600 x 245*	1680 x 600 x 245*	2005 x 600 x 245*
Total Connected Load	1.2kW	1.8kW	2.4kW	2.4kW	2.4kW
Electrical Connection	240VAC / 50Hz (10A plug & lead)	240VAC / 50Hz (10A plug & lead)	240VAC / 50Hz (10A plug & lead)	240VAC / 50Hz (10A plug & lead)	240VAC / 50Hz (10A plug & lead)
Bain Marie Capacity	4 x 1/2 GN Pans	6 x 1/2 GN Pans	8 x 1/2 GN Pans	10 x 1/2 GN Pans	12 x 1/2 GN Pans

*Dimension does not include tap

